

# Package: Quandl (via r-universe)

September 14, 2024

**Title** API Wrapper for Quandl.com

**Version** 2.11.0

**Date** 2021-08-11

**Maintainer** Dave Dotson <dave@quandl.com>

**Description** Functions for interacting directly with the Quandl API to offer data in a number of formats usable in R, downloading a zip with all data from a Quandl database, and the ability to search. This R package uses the Quandl API. For more information go to <<https://docs.quandl.com>>. For more help on the package itself go to <<https://www.quandl.com/tools/r>>.

**Imports** htr (>= 0.6.1), zoo, jsonlite (>= 0.9.14)

**Suggests** testthat (>= 0.10.0), roxygen2, timeSeries

**Depends** R (>= 2.15.0), xts

**License** MIT + file LICENSE

**URL** <https://github.com/quandl/quandl-r>

**BugReports** <https://github.com/quandl/quandl-r/issues>

**RoxygenNote** 7.1.1

**Repository** <https://quandl.r-universe.dev>

**RemoteUrl** <https://github.com/quandl/quandl-r>

**RemoteRef** HEAD

**RemoteSha** d88c1dc30786a3d628f19de2f2f2bc73fbaeac09

## Contents

metaData . . . . .	2
Quandl . . . . .	3
quandl.api . . . . .	4
Quandl.api_key . . . . .	5
Quandl.auth . . . . .	6
Quandl.base_url . . . . .	6

Quandl.database.bulk_download_to_file . . . . .	7
Quandl.database.bulk_download_url . . . . .	8
Quandl.dataset.get . . . . .	9
Quandl.datatable . . . . .	10
Quandl.datatable.bulk_download_to_file . . . . .	11
Quandl.datatable.bulk_download_url . . . . .	12
Quandl.pit.asofdate . . . . .	13
Quandl.pit.between . . . . .	14
Quandl.pit.fromto . . . . .	15
Quandl.search . . . . .	16

<b>Index</b>	<b>17</b>
--------------	-----------

---

metaData	<i>Retrieve metadata from a Quandl series or search results</i>
----------	---

---

## Description

Retrieve metadata from a Quandl series or search results

## Usage

```
metaData(x)
```

## Arguments

x                    A Quandl time series object or search results with attached meta data.

## Value

Returns a list of meta data about the series or search results.

## See Also

[Quandl](#), [Quandl.search](#)

## Examples

```
## Not run:
metaData(ts)

## End(Not run)
```

---

 Quandl

*Retrieves Data from the Quandl Dataset endpoint and formats*


---

**Description**

Retrieves Data from the Quandl Dataset endpoint and formats

**Usage**

```

Quandl(
  code,
  type = c("raw", "ts", "zoo", "xts", "timeSeries"),
  transform = c("", "diff", "rdiff", "normalize", "cumul", "rdiff_from"),
  collapse = c("", "daily", "weekly", "monthly", "quarterly", "annual"),
  order = c("desc", "asc"),
  meta = FALSE,
  force_irregular = FALSE,
  ...
)

```

**Arguments**

code	Dataset code on Quandl specified as a string or an array of strings.
type	Type of data returned specified as string. Can be 'raw', 'ts', 'zoo', 'xts' or 'timeSeries'.
transform	Apply Quandl API data transformations.
collapse	Collapse frequency of Data.
order	Select if data is given to R in ascending or descending formats. Helpful for the rows parameter.
meta	Adds meta data as an attribute to the returned Data.
force_irregular	When set to TRUE, forces the index of the Data to be of date format yyyy-mm-dd
...	Additional named values that are interpreted as Quandl API parameters. Please see <a href="https://docs.quandl.com/docs/in-depth-usage#get-time-series-metadata">https://docs.quandl.com/docs/in-depth-usage#get-time-series-metadata</a> for a full list of parameters.

**Details**

Set your `api_key` with `Quandl.api_key` function. For instructions on finding your api key go to <https://www.quandl.com/account/profile>.

**Value**

Depending on the type the class is either `data.frame`, `time series`, `xts`, `zoo` or `timeSeries`.

## References

This R package uses the Quandl API. For more information go to <https://docs.quandl.com>. For more help on the package itself go to <https://www.quandl.com/tools/r>.

## See Also

[Quandl.api\\_key](#)

## Examples

```
## Not run:
quandldata = Quandl("NSE/OIL", collapse="monthly", start_date="2013-01-01", type="ts")
plot(quandldata[,1])

## End(Not run)
```

---

quandl.api

*Executes Quandl API calls*

---

## Description

Executes Quandl API calls

## Usage

```
quandl.api(
  path,
  http = c("GET", "PUT", "POST", "DELETE"),
  postdata = NULL,
  ...
)
```

## Arguments

path	Path to api resource.
http	Type of http request sent.
postdata	A character or raw vector that is sent in a body.
...	Named values that are interpreted as Quandl API parameters. Please see <a href="https://docs.quandl.com">https://docs.quandl.com</a> .

## Details

Set your api\_key with `Quandl.api_key` function. For instructions on finding your api key go to <https://www.quandl.com/account/profile>

## Value

Quandl API response.

**See Also**

[Quandl.api\\_key](#)

**Examples**

```
## Not run:
quandldata = quandl.api(path="datasets/NSE/OIL", http="GET")
plot(quandldata[,1])

## End(Not run)
```

---

Quandl.api_key	<i>Query or set Quandl API key</i>
----------------	------------------------------------

---

**Description**

Query or set Quandl API key

**Usage**

```
Quandl.api_key(api_key)
```

**Arguments**

api\_key      Optionally passed parameter to set Quandl api\_key.

**Value**

Returns invisibly the currently set api\_key.

**Examples**

```
## Not run:
Quandl.api_key('foobar')

## End(Not run)
```

---

Quandl.auth                      *Query or set Quandl API token*

---

**Description**

Deprecated. Alias of [Quandl.api\\_key](#)

**Usage**

```
Quandl.auth(auth_token)
```

**Arguments**

auth\_token            Optionally passed parameter to set Quandl auth\_token.

**Value**

Returns invisibly the currently set auth\_token.

**See Also**

[Quandl](#)

**Examples**

```
## Not run:  
Quandl.auth('foobar')  
  
## End(Not run)
```

---

Quandl.base\_url                      *Query or set Base URL for White-labeled sites*

---

**Description**

Query or set Base URL for White-labeled sites

**Usage**

```
Quandl.base_url(base_url)
```

**Arguments**

base\_url              Optionally passed parameter to set Quandl base\_url.

**Value**

Returns invisibly the currently set base\_url.

**Examples**

```
## Not run:  
Quandl.base_url('http://localhost')  
  
## End(Not run)
```

---

```
Quandl.database.bulk_download_to_file  
Downloads a zip with all data from a Quandl database
```

---

**Description**

Downloads a zip with all data from a Quandl database

**Usage**

```
Quandl.database.bulk_download_to_file(database_code, filename, ...)
```

**Arguments**

database_code	Database code on Quandl specified as a string.
filename	Filename (including path) of file to download.
...	Additional named values that are interpreted as Quandl API parameters. Please see <a href="https://docs.quandl.com/docs/parameters-2">https://docs.quandl.com/docs/parameters-2</a> for a full list of parameters.

**Details**

Set your api\_key with Quandl.api\_key function. For instructions on finding your api key go to <https://www.quandl.com/account/profile>

**Value**

The filename of the downloaded file.

**See Also**

[Quandl.api\\_key](#)

**Examples**

```
## Not run:  
Quandl.database.bulk_download_to_file("NSE", "./NSE.zip")  
  
## End(Not run)
```

---

Quandl.database.bulk\_download\_url

*Returns the bulk download url*

---

## Description

Returns the bulk download url

## Usage

```
Quandl.database.bulk_download_url(database_code, ...)
```

## Arguments

database\_code Database code on Quandl specified as a string.

... Additional named values that are interpreted as Quandl API parameters. Please see <https://docs.quandl.com/docs/parameters-2> for a full list of parameters.

## Details

Set your api\_key with Quandl.api\_key function. For instructions on finding your api key go to <https://www.quandl.com/account/profile>

## Value

Returns the download url.

## See Also

[Quandl.api\\_key](#)

## Examples

```
## Not run:  
url = Quandl.database.download_url("NSE", download_type="partial")  
  
## End(Not run)
```



---

Quandl.dataset.get      *Retrieves Data from the Quandl Dataset endpoint*

---

### Description

Retrieves Data from the Quandl Dataset endpoint

### Usage

```
Quandl.dataset.get(code, params)
```

### Arguments

code	Dataset code on Quandl specified as a string.
params	A list of parameters to be passed to the Quandl API. Please see <a href="https://docs.quandl.com/docs/in-depth-usage#get-time-series-metadata">https://docs.quandl.com/docs/in-depth-usage#get-time-series-metadata</a> for a full list of parameters.

### Details

Set your `api_key` with `Quandl.api_key` function. For instructions on finding your api key go to <https://www.quandl.com/account/profile>

### Value

Returns a data.frame of the requested data

### See Also

[Quandl.api\\_key](#), [Quandl](#)

### Examples

```
## Not run:  
quandldata = Quandl.dataset.get("NSE/OIL", list(rows=5))  
plot(quandldata[,1])  
  
## End(Not run)
```

---

Quandl.datatable	<i>Retrieves Data from the Quandl Datatable endpoint</i>
------------------	--

---

### Description

Retrieves Data from the Quandl Datatable endpoint

### Usage

```
Quandl.datatable(datatable_code, paginate = FALSE, ...)
```

### Arguments

`datatable_code` Datatable code on Quandl specified as a string.  
`paginate` When set to TRUE, fetches up to 1,000,000 rows of data  
`...` Additional named values that are interpreted as Quandl API parameters.

### Details

Set your `api_key` with `Quandl.api_key` function. For instructions on finding your api key go to <https://www.quandl.com/account/profile>

### Value

Returns a `data.frame`.

### See Also

[Quandl.api\\_key](#)

### Examples

```
## Not run:  
Quandl.datatable('ZACKS/FC', paginate=TRUE)  
  
## End(Not run)
```

---

`Quandl.datatable.bulk_download_to_file`*Downloads a zip with all data requested from a Quandl database*

---

### Description

Downloads a zip with all data requested from a Quandl database

### Usage

```
Quandl.datatable.bulk_download_to_file(datatable_code, filename, ...)
```

### Arguments

`datatable_code` Datatable code on Quandl specified as a string.  
`filename` Filename (including path) of file to download.  
`...` Additional named values that are interpreted as Quandl API parameters.

### Details

Set your `api_key` with `Quandl.api_key` function. For instructions on finding your api key go to <https://www.quandl.com/account/profile>

### Value

Returns a `data.frame`.

### See Also

[Quandl.api\\_key](#)

### Examples

```
## Not run:  
Quandl.datatable.bulk_download_to_file('ZACKS/EE')  
  
## End(Not run)
```

---

Quandl.datatable.bulk\_download\_url

*Generates and returns a bulk download url*

---

## Description

Generates and returns a bulk download url

## Usage

```
Quandl.datatable.bulk_download_url(datatable_code, ...)
```

## Arguments

`datatable_code` Datatable code on Quandl specified as a string.

`...` Additional named values that are interpreted as Quandl API parameters. Please see <https://docs.quandl.com/docs/parameters-1> for a full list of parameters.

## Details

Set your `api_key` with `Quandl.api_key` function. For instructions on finding your api key go to <https://www.quandl.com/account/profile>

## Value

Returns the download url.

## See Also

[Quandl.api\\_key](#)

## Examples

```
## Not run:  
url = Quandl.datatable.bulk_download_url("ZACKS/EE", ticker="AAPL")  
  
## End(Not run)
```

---

Quandl.pit.asofdate *Retrieves Point In Time Data from the Quandl PIT endpoint. As of date is used to see the table as it was at a specific point in time in the past.*

---

### Description

Retrieves Point In Time Data from the Quandl PIT endpoint. As of date is used to see the table as it was at a specific point in time in the past.

### Usage

```
Quandl.pit.asofdate(datatable_code, start_date, paginate = FALSE, ...)
```

### Arguments

`datatable_code` Datatable code on Quandl specified as a string.  
`start_date` Lower date as a string.  
`paginate` When set to TRUE, fetches up to 1,000,000 rows of data  
`...` Additional named values that are interpreted as Quandl API parameters.

### Details

Set your `api_key` with `Quandl.api_key` function. For instructions on finding your api key go to <https://www.quandl.com/account/profile>

### Value

Returns a `data.frame`.

### See Also

[Quandl.api\\_key](#)

### Examples

```
## Not run:  
Quandl.pit.asofdate('RSM/MSB', '2020-06-11', paginate=TRUE)  
  
## End(Not run)
```

Quandl.pit.between *Retrieves Point In Time Data from the Quandl PIT endpoint. Between start and end will show all rows that were visible at any point between two specified points in time. It works inclusively, a row visible exactly at start or exactly at end will be shown too.*

---

### Description

Retrieves Point In Time Data from the Quandl PIT endpoint. Between start and end will show all rows that were visible at any point between two specified points in time. It works inclusively, a row visible exactly at start or exactly at end will be shown too.

### Usage

```
Quandl.pit.between(datatable_code, start_date, end_date, paginate = FALSE, ...)
```

### Arguments

datatable\_code Datatable code on Quandl specified as a string.  
start\_date Lower date as a string.  
end\_date Upper date as a string.  
paginate When set to TRUE, fetches up to 1,000,000 rows of data  
... Additional named values that are interpreted as Quandl API parameters.

### Details

Set your api\_key with Quandl.api\_key function. For instructions on finding your api key go to <https://www.quandl.com/account/profile>

### Value

Returns a data.frame.

### See Also

[Quandl.api\\_key](#)

### Examples

```
## Not run:  
Quandl.pit.between('RSM/MSB', '2020-06-11', '2020-06-12', paginate=TRUE)  
  
## End(Not run)
```

---

Quandl.pit.fromto	<i>Retrieves Point In Time Data from the Quandl PIT endpoint. From start to end will also show all rows that were visible at any point between two specified points in time, including start, but excluding end.</i>
-------------------	--

---

### Description

Retrieves Point In Time Data from the Quandl PIT endpoint. From start to end will also show all rows that were visible at any point between two specified points in time, including start, but excluding end.

### Usage

```
Quandl.pit.fromto(datatable_code, start_date, end_date, paginate = FALSE, ...)
```

### Arguments

<code>datatable_code</code>	Datatable code on Quandl specified as a string.
<code>start_date</code>	Lower date as a string.
<code>end_date</code>	Upper date as a string.
<code>paginate</code>	When set to TRUE, fetches up to 1,000,000 rows of data
<code>...</code>	Additional named values that are interpreted as Quandl API parameters.

### Details

Set your `api_key` with `Quandl.api_key` function. For instructions on finding your api key go to <https://www.quandl.com/account/profile>

### Value

Returns a `data.frame`.

### See Also

[Quandl.api\\_key](#)

### Examples

```
## Not run:  
Quandl.pit.fromto('RSM/MSB', '2020-06-11', '2020-06-12', paginate=TRUE)  
  
## End(Not run)
```

---

Quandl.search      *Search the Quandl database*

---

**Description**

Search the Quandl database

**Usage**

```
Quandl.search(query, silent = FALSE, per_page = 10, ...)
```

**Arguments**

query	Search terms
silent	Prints the results when FALSE.
per_page	Number of results returned per page.
...	Additional named values that are interpreted as Quandl API parameters.

**Details**

Set your `api_key` with `Quandl.api_key` function. For instructions on finding your api key go to <https://www.quandl.com/account/profile>

For instructions on finding your authentication token go to <https://www.quandl.com/account/profile>

**Value**

Search results returned as a `data.frame`.

**See Also**

[Quandl.api\\_key](#)

**Examples**

```
## Not run:  
search.results <- Quandl.search("oil")  
  
## End(Not run)
```



# Index

`metaData`, [2](#)

`Quandl`, [2](#), [3](#), [6](#), [9](#)

`quandl.api`, [4](#)

`Quandl.api_key`, [4](#), [5](#), [5](#), [6–16](#)

`Quandl.auth`, [6](#)

`Quandl.base_url`, [6](#)

`Quandl.database.bulk_download_to_file`,  
[7](#)

`Quandl.database.bulk_download_url`, [8](#)

`Quandl.dataset.get`, [9](#)

`Quandl.datatable`, [10](#)

`Quandl.datatable.bulk_download_to_file`,  
[11](#)

`Quandl.datatable.bulk_download_url`, [12](#)

`Quandl.pit.asofdate`, [13](#)

`Quandl.pit.between`, [14](#)

`Quandl.pit.fromto`, [15](#)

`Quandl.search`, [2](#), [16](#)